


# VTXS 10.0530.25

Vale-Tu Square XSmall (1xLED 12W 830/3000K 790lm)

— C0/C180 cd / 1000 lm



|              | C0   | C90  | C180 | C270 |
|--------------|------|------|------|------|
| 0°           | 2294 | 2294 | 2294 | 2294 |
| 15°          | 1442 | 1442 | 1442 | 1442 |
| 30°          | 334  | 334  | 334  | 334  |
| 45°          | 26   | 26   | 26   | 26   |
| 60°          | 1    | 1    | 1    | 1    |
| 75°          | 0    | 0    | 0    | 0    |
| 90°          | 0    | 0    | 0    | 0    |
| cd / 1000 lm |      |      |      |      |

Offset [m] Cone width [m] Illuminance [lx]

| C0-C180 Plane |      |       |
|---------------|------|-------|
| 3.0           | 1.96 | 201.4 |
| 6.0           | 3.92 | 50.3  |
| 9.0           | 5.88 | 22.4  |
| 12.0          | 7.83 | 12.6  |
| 15.0          | 9.79 | 8.1   |

|                    |                    |
|--------------------|--------------------|
| <b>η</b>           | LED                |
| Efficiency         | 66 lm/W            |
| Direct/Indirect    | ↓ 100% / ↑ 0%      |
| System Power       | 12 W               |
| <b>UGR</b>         | X=4H, Y=8H         |
| Reflection factors | 70/50/20           |
| UGR C0/C180        | 17.2               |
| UGR C90/C270       | 17.2               |
| CIE Flux Codes     | 98 100 100 100 100 |
| Ra/CRI             | >80                |