

## Flush-mounting installation boxes



UPPLUS



### Flush mounting one-gang junction box, Depth 66 mm

- dimensions in accordance with German DIN 49073
- For M20/M25 conduits and cables

<b>Article no:</b>	<b>1555-04</b>
EAN:	4013456120617
Depth	66 mm
Screw spacing	60 mm
Conduit entries M20	9
Number of screw domes	4
Splayed claw fields	2
Conduit entries M25	2
Combination conduit entries M20/25	2
Halogen-free	Yes
Packaging inner/dispatch	25/250

With the innovative KAISER UP-PLUS technology, the flush-mounting range impresses with a PLUS in terms of fitting convenience and flexibility. This range with the practical combination connection piece for quick, safe combinations ensures a torsion-proof pluggable connection for combinations with the snap-in connector, as well as a guaranteed standardised combination distance of 71 mm. The variable combination connection pieces are suitable for M20/M25 conduits and cables, and are standard for KAISER flush-mounting boxes. There are further entries for M20/M25 conduits and cables around the circumference of the box, as well as an entry for M20 conduits or cables at the bottom of the box. Four screw domes and two expanding claw fields offer secure, flexible mounting options for all types of devices, and thus round off the flush-mounting range.

- Variable combination connection piece for conduits up to M25 and cables
- Snap-in connector for torsion-proof and guaranteed standardised combination distance of 71 mm
- Flexible for screw and expanding claw fixing
- Optimum installation space
- UP-PLUS – with distance support, tunnel connector and KLEMMFIX® for quick, secure installation

